



ALARM SAF

RM-2416F

24 VAC

16 Fused Outputs

Rack Mount Power Supplies

for CCTV Cameras and Accessories



24 VAC, 12.5 Amp Rack Mount power supply with 16 fuse protected outputs. Ideal for CCTV applications in retail, health care, gaming, entertainment, transportation, government and educational facilities.

Designed to fit neatly into standard video equipment racks, the streamlined cabinetry and exceptional features combine to significantly reduce installation and service costs. Features include removable terminal strips for field wiring, input and output surge suppression, automotive blade fuses for improved reliability and a removable chassis face plate for serviceability.

ORDER NUMBER	MODEL NUMBER	DESCRIPTION
03002	RM-2416F	24 VAC, 12.5 A, rack mount power supply with 16 fused outputs
03013	RM-UWB	Universal wall mount bracket

AGENCY LISTINGS

- LISTED TO: UL/ANSI 2044, 2nd edition, current revision
- CERTIFIED TO: CAN/CSA STD C22.2 No. 1-98

FEATURES

- 16 individually fused outputs
- Illuminated master power switch with circuit breaker
- 24 VAC
- Input and output surge suppression
- Externally visible LED indicators per zone
- Maintains camera synchronization
- Standard, 2U EIA 19" rack mount chassis
- Removable face plate for easy serviceability
- Removable terminal strips for field wiring
- Automotive blade fuses for improved reliability
- Spare fuses included
- Removable 3 wire grounded AC line cord
- Optional hardwire capability
- Universal wall mount bracket available
- Limited lifetime warranty

APPLICATIONS

- Digital color cameras
- Monochrome cameras
- Indoor/outdoor fixed domes
- PTZ's
- IP cameras
- Fiber optic senders/receivers

SPECIFICATIONS

Input Specifications:

- Input voltage: 120 VAC
- Input voltage frequency: 60 Hz
- Input current: 2.5 A

Output Specifications:

- Output voltage: 24 VAC
- Total output current: 12.5 A
- Outputs: 16 fused outputs
- Fuse rating: 3A

Temperature Ratings:

- Operating temperature: 0 °C to 49 °C
- Humidity: 85% @ 30 °C
- BTU/hr: 58

Visual Indication:

- AC presence: Lighted AC switch
- Zone output: Green LED per zone

MECHANICAL

- 2U rack mount chassis:
3.25" H x 19.125" W x 10" D
- 16 gauge galvanized steel