




ALARM SAF

RM-28XF-300

24 or 28 VAC Selectable per Output
16 or 32 Fused Outputs
Rack Mount Power Supplies
for CCTV Cameras and Accessories



24/28 VAC, 12.5/10 Amp Rack Mount power supply with either 16 or 32 fuse protected outputs. Ideal for CCTV applications in retail, health care, gaming, entertainment, transportation, government and educational facilities.

The RM-28 series delivers maximum flexibility for large multi-camera projects by providing increased current capability and allowing the user to select either 24 VAC or 28 VAC on each output .

Designed to fit neatly into standard video equipment racks, the streamlined cabinetry and exceptional features combine to significantly reduce installation and service costs. Features include removable terminal strips for field wiring, input and output surge suppression, automotive blade fuses for improved reliability and a removable chassis face plate for serviceability.

ORDER NUMBER	MODEL NUMBER	DESCRIPTION
03007	RM-2816F-300	24/28 VAC, 12.5/10 A, rack mount power supply with 16 fused outputs
03011	RM-2832F-300	24/28 VAC, 12.5/10 A, rack mount power supply with 32 fused outputs
03013	RM-UWB	Universal wall mount bracket

AGENCY LISTINGS

- CONFORMS TO: ANSI/UL 2044
- CERTIFIED TO: CSA STD C22.2 No. 1

FEATURES

- 16 or 32 individually fused outputs
- 24 or 28 VAC selectable per output by positional jumper
- Illuminated master power switch with circuit breaker
- Input and output surge suppression
- Externally visible LED indicators per zone
- Removable jumper for individual output disconnect
- Maintains camera synchronization
- Standard, 2U EIA 19" rack mount chassis
- Removable face plate for easy serviceability
- Removable terminal strips for field wiring
- Automotive blade fuses for improved reliability
- Spare fuses included
- Removable 3 wire grounded AC line cord
- Optional hardwire capability
- Universal wall mount bracket available
- Limited lifetime warranty

APPLICATIONS

- Digital color cameras
- Monochrome cameras
- Indoor/outdoor fixed domes
- PTZ's
- IP cameras
- Fiber optic senders/receivers

SPECIFICATIONS

Input Specifications:

- Input voltage: 120 VAC
- Input voltage frequency: 60 Hz
- Input current: 2.5 A

Output Specifications:

- Output voltage: 24 VAC or 28 VAC
- Output current: 12.5 A @ 24 VAC
10 A @ 28 VAC

RM-2816F-300

- Outputs: 16 fused outputs
- Fuse rating: 3A

RM-2832F-300

- Outputs: 32 fused outputs
- Fuse rating: 3A

Temperature Ratings:

- Operating temperature: 0 °C to 49 °C
- Humidity: 85% @ 30 °C
- BTU/hr: 58

Visual Indication:

- AC presence: Lighted AC switch
- Zone output: Green LED per zone

MECHANICAL

- 2U rack mount chassis:
3.25" H x 19.125" W x 10" D
- 16 gauge galvanized steel